



(1) Publication number:

0 430 469 A3

(12)

EUROPEAN PATENT APPLICATION

(21) Application number: 90312233.1

(51) Int. Cl.5: H04B 1/16, H03J 7/22

② Date of filing: 08.11.90

Priority: 30.11.89 US 443624

43 Date of publication of application: 05.06.91 Bulletin 91/23

Designated Contracting States:
DE FR GB

Date of deferred publication of the search report: 27.05.92 Bulletin 92/22

 Applicant: FORD MOTOR COMPANY LIMITED Eagle Way
 Brentwood Essex CM13 3BW(GB)

Applicant: FORD-WERKE AKTIENGESELLSCHAFT Werk Köln-Niehl Henry-Ford-Strasse Postfach 60 40 02 W-5000 Köln 60(DE)

⊗ DE

Applicant: FORD FRANCE S. A. B.P. 307 F-92506 Rueil-Malmalson Cédex(FR)


(⊌) FR

② Inventor: Kennedy, John Francis 30453 Sheridan Garden City, Michigan 48135(US) Inventor: Kuo, Yao Hsien 45144 Brunswick Drive Canton, Michigan 48187(US)

Representative: Messulam, Alec Moses et al A. Messulam & Co. 24 Broadway Leigh on Sea Essex SS9 1BN(GB)

(A) A signal quality detecting circuit for FM receivers.

57 A signal quality detecting circuit for an FM receiver, said receiver including an IF detector generating an intensity signal indicating the received field strength of the FM signal being received and including an FM demodulator generating an automatic frequency control signal indicating a frequency error at which said FM signal is being received, said signal quality detecting circuit comprising, level detector means (32) adapted to be coupled to said IF detector for producing a first signal when said intensity signal is greater than a predetermined intensity, window detector means (33) adapted to be coupled to said FM demodulator for producing a second signal when said automatic frequency control signal is within a predetermined window, noise filter means (31) adapted to be coupled to said IF detector for generating a filtered noise signal derived from said intensity signal, said filter means rejecting frequencies containing components related to the intelligence contained in said FM signal, peak detector means (31) coupled to said noise filter means for producing a third signal when said filtered noise signal is below a predetermined peak value, and logic means coupled to said level detector means, said window detector means, and said peak detector means for producing an indicating signal (35) in response to the simultaneous occurrence of said first, second, and third signals to indicate that a high quality FM signal is being received.



EP 90 31 2233

DOCUMENTS CONSIDERED TO BE RELEVANT					
Category	Citation of document with indic of relevant passa	ation, where appropriate,	Relevant to claim	CLASSIFICATION OF THE APPLICATION (Int. CL5)	
A	IEEE TRANSACTIONS ON COMS vol. CE28, no. 3, August pages 383 - 392; WILE: 'advanced fm-if' * page 383, line 18 - lin * page 386, line 34 - pag	1982, NEW YORK US e 41; figures 1,5,6,7 *	1,7,8	HO4B1/16 HO3J7/22	
A	PATENT ABSTRACTS OF JAPAN vol. 8, no. 84 (E-239)(15 & JP-A-59 005 730 (MITSU * abstract *	i21) 18 April 1984	1,7,8		
A	WS-A-3 934 206 (HOLECEK) * column 2, line 21 - line * abstract *	ne 47; figure *	1,2,5,6, 7,11		
A	US-A-4 293 736 (OGITA) * column 1, line 16 - lin * column 4, line 32 - lin		3	TECHNICAL FIELDS	
A	US-A-4 087 641 (SUGAI) * column 1, line 6 - line	a 43 *	9,10	SEARCHED (Int. Cl.5)	
A	EP-A-0 335 141 (BLAU-PUNI * claims 1,2 *	KT CMBH)	1,7,11	HO3J	
[The present search report has been			Reminer	
Place of search Data of complation of the search					
Y:p:	THE HAGUE CATEGORY OF CITED DOCUMEN articularly relevant if taken alone articularly relevant if combined with anot scament of the same category schnological background	ster the filing ber D : document cite L : document cite	iple underlying to ocument, but put date in the applicati	0R 15	
0:b	on-written disclosure	& : member of the document	same patent fan	ally, corresponding	